

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 600V

|               |        |     |    |   |
|---------------|--------|-----|----|---|
| M49467P07100J | 10 pF  | 5%  | BP | A |
| M49467P07100K | 10 pF  | 10% | BP | A |
| M49467P07120J | 12 pF  | 5%  | BP | A |
| M49467P07120K | 12 pF  | 10% | BP | A |
| M49467P07150J | 15 pF  | 5%  | BP | A |
| M49467P07150K | 15 pF  | 10% | BP | A |
| M49467P07180J | 18 pF  | 5%  | BP | A |
| M49467P07180K | 18 pF  | 10% | BP | A |
| M49467P07220J | 22 pF  | 5%  | BP | A |
| M49467P07220K | 22 pF  | 10% | BP | A |
| M49467P07270J | 27 pF  | 5%  | BP | A |
| M49467P07270K | 27 pF  | 10% | BP | A |
| M49467P07330J | 33 pF  | 5%  | BP | A |
| M49467P07330K | 33 pF  | 10% | BP | A |
| M49467P07390J | 39 pF  | 5%  | BP | A |
| M49467P07390K | 39 pF  | 10% | BP | A |
| M49467P07470J | 47 pF  | 5%  | BP | A |
| M49467P07470K | 47 pF  | 10% | BP | A |
| M49467P07560J | 56 pF  | 5%  | BP | A |
| M49467P07560K | 56 pF  | 10% | BP | A |
| M49467P07680J | 68 pF  | 5%  | BP | A |
| M49467P07680K | 68 pF  | 10% | BP | A |
| M49467P07820J | 82 pF  | 5%  | BP | A |
| M49467P07820K | 82 pF  | 10% | BP | A |
| M49467P07101J | 100 pF | 5%  | BP | A |
| M49467P07101K | 100 pF | 10% | BP | A |
| M49467R07101K | 100 pF | 10% | BR | A |
| M49467R07101M | 100 pF | 20% | BR | A |
| M49467P07121J | 120 pF | 5%  | BP | A |
| M49467P07121K | 120 pF | 10% | BP | A |
| M49467R07121K | 120 pF | 10% | BR | A |
| M49467R07121M | 120 pF | 20% | BR | A |
| M49467P07151J | 150 pF | 5%  | BP | A |
| M49467P07151K | 150 pF | 10% | BP | A |
| M49467R07151K | 150 pF | 10% | BR | A |
| M49467R07151M | 150 pF | 20% | BR | A |
| M49467P07181J | 180 pF | 5%  | BP | A |
| M49467P07181K | 180 pF | 10% | BP | A |
| M49467R07181K | 180 pF | 10% | BR | A |
| M49467R07181M | 180 pF | 20% | BR | A |
| M49467P07221J | 220 pF | 5%  | BP | A |
| M49467P07221K | 220 pF | 10% | BP | A |
| M49467R07221K | 220 pF | 10% | BR | A |
| M49467R07221M | 220 pF | 20% | BR | A |
| M49467P07271J | 270 pF | 5%  | BP | A |
| M49467P07271K | 270 pF | 10% | BP | A |
| M49467R07271K | 270 pF | 10% | BR | A |
| M49467R07271M | 270 pF | 20% | BR | A |
| M49467P07331J | 330 pF | 5%  | BP | A |
| M49467P07331K | 330 pF | 10% | BP | A |
| M49467R07331K | 330 pF | 10% | BR | A |
| M49467R07331M | 330 pF | 20% | BR | A |
| M49467P07391J | 390 pF | 5%  | BP | A |
| M49467P07391K | 390 pF | 10% | BP | A |
| M49467R07391K | 390 pF | 10% | BR | A |
| M49467R07391M | 390 pF | 20% | BR | A |
| M49467P07471J | 470 pF | 5%  | BP | A |
| M49467P07471K | 470 pF | 10% | BP | A |
| M49467R07471K | 470 pF | 10% | BR | A |
| M49467R07471M | 470 pF | 20% | BR | A |
| M49467P07561J | 560 pF | 5%  | BP | A |
| M49467P07561K | 560 pF | 10% | BP | A |
| M49467R07561K | 560 pF | 10% | BR | A |
| M49467R07561M | 560 pF | 20% | BR | A |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 600V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467P07681J | 680 pF   | 5%  | BP | A |
| M49467P07681K | 680 pF   | 10% | BP | A |
| M49467R07681K | 680 pF   | 10% | BR | A |
| M49467R07681M | 680 pF   | 20% | BR | A |
| M49467P07821J | 820 pF   | 5%  | BP | A |
| M49467P07821K | 820 pF   | 10% | BP | A |
| M49467R07821K | 820 pF   | 10% | BR | A |
| M49467R07821M | 820 pF   | 20% | BR | A |
| M49467P07102J | 1000 pF  | 5%  | BP | A |
| M49467P07102K | 1000 pF  | 10% | BP | A |
| M49467R07102K | 1000 pF  | 10% | BR | A |
| M49467R07102M | 1000 pF  | 20% | BR | A |
| M49467P07122J | 1200 pF  | 5%  | BP | A |
| M49467P07122K | 1200 pF  | 10% | BP | A |
| M49467R07122K | 1200 pF  | 10% | BR | A |
| M49467R07122M | 1200 pF  | 20% | BR | A |
| M49467P07152J | 1500 pF  | 5%  | BP | A |
| M49467P07152K | 1500 pF  | 10% | BP | A |
| M49467R07152K | 1500 pF  | 10% | BR | A |
| M49467R07152M | 1500 pF  | 20% | BR | A |
| M49467P07182J | 1800 pF  | 5%  | BP | A |
| M49467P07182K | 1800 pF  | 10% | BP | A |
| M49467R07182K | 1800 pF  | 10% | BR | A |
| M49467R07182M | 1800 pF  | 20% | BR | A |
| M49467P07222J | 2200 pF  | 5%  | BP | A |
| M49467P07222K | 2200 pF  | 10% | BP | A |
| M49467R07222K | 2200 pF  | 10% | BR | A |
| M49467R07222M | 2200 pF  | 20% | BR | A |
| M49467P07272J | 2700 pF  | 5%  | BP | A |
| M49467P07272K | 2700 pF  | 10% | BP | A |
| M49467R07272K | 2700 pF  | 10% | BR | A |
| M49467R07272M | 2700 pF  | 20% | BR | A |
| M49467P07332J | 3300 pF  | 5%  | BP | A |
| M49467P07332K | 3300 pF  | 10% | BP | A |
| M49467R07332K | 3300 pF  | 10% | BR | A |
| M49467R07332M | 3300 pF  | 20% | BR | A |
| M49467P07392J | 3900 pF  | 5%  | BP | A |
| M49467P07392K | 3900 pF  | 10% | BP | A |
| M49467R07392K | 3900 pF  | 10% | BR | A |
| M49467R07392M | 3900 pF  | 20% | BR | A |
| M49467P07472J | 4700 pF  | 5%  | BP | A |
| M49467P07472K | 4700 pF  | 10% | BP | A |
| M49467R07472K | 4700 pF  | 10% | BR | A |
| M49467R07472M | 4700 pF  | 20% | BR | A |
| M49467P07562J | 5600 pF  | 5%  | BP | A |
| M49467P07562K | 5600 pF  | 10% | BP | A |
| M49467R07562K | 5600 pF  | 10% | BR | A |
| M49467R07562M | 5600 pF  | 20% | BR | A |
| M49467P07682J | 6800 pF  | 5%  | BP | B |
| M49467P07682K | 6800 pF  | 10% | BP | B |
| M49467R07682K | 6800 pF  | 10% | BR | A |
| M49467R07682M | 6800 pF  | 20% | BR | A |
| M49467P07822J | 8200 pF  | 5%  | BP | B |
| M49467P07822K | 8200 pF  | 10% | BP | B |
| M49467R07822K | 8200 pF  | 10% | BR | A |
| M49467R07822M | 8200 pF  | 20% | BR | A |
| M49467P07103J | 0.01 μF  | 5%  | BP | B |
| M49467P07103K | 0.01 μF  | 10% | BP | B |
| M49467R07103K | 0.01 μF  | 10% | BR | A |
| M49467R07103M | 0.01 μF  | 20% | BR | A |
| M49467P07123J | 0.012 μF | 5%  | BP | B |
| M49467P07123K | 0.012 μF | 10% | BP | B |
| M49467R07123K | 0.012 μF | 10% | BR | A |
| M49467R07123M | 0.012 μF | 20% | BR | A |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 600V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467P07153J | 0.015 μF | 5%  | BP | C |
| M49467P07153K | 0.015 μF | 10% | BP | C |
| M49467R07153K | 0.015 μF | 10% | BR | A |
| M49467R07153M | 0.015 μF | 20% | BR | A |
| M49467P07183J | 0.018 μF | 5%  | BP | D |
| M49467P07183K | 0.018 μF | 10% | BP | D |
| M49467R07183K | 0.018 μF | 10% | BR | A |
| M49467R07183M | 0.018 μF | 20% | BR | A |
| M49467P07223J | 0.022 μF | 5%  | BP | D |
| M49467P07223K | 0.022 μF | 10% | BP | D |
| M49467R07223K | 0.022 μF | 10% | BR | A |
| M49467R07223M | 0.022 μF | 20% | BR | A |
| M49467P07273J | 0.027 μF | 5%  | BP | D |
| M49467P07273K | 0.027 μF | 10% | BP | D |
| M49467R07273K | 0.027 μF | 10% | BR | A |
| M49467R07273M | 0.027 μF | 20% | BR | A |
| M49467P07333J | 0.033 μF | 5%  | BP | D |
| M49467P07333K | 0.033 μF | 10% | BP | D |
| M49467R07333K | 0.033 μF | 10% | BR | B |
| M49467R07333M | 0.033 μF | 20% | BR | B |
| M49467P07393J | 0.039 μF | 5%  | BP | D |
| M49467P07393K | 0.039 μF | 10% | BP | D |
| M49467R07393K | 0.039 μF | 10% | BR | B |
| M49467R07393M | 0.039 μF | 20% | BR | B |
| M49467P07473J | 0.047 μF | 5%  | BP | E |
| M49467P07473K | 0.047 μF | 10% | BP | E |
| M49467R07473K | 0.047 μF | 10% | BR | B |
| M49467R07473M | 0.047 μF | 20% | BR | B |
| M49467P07563J | 0.056 μF | 5%  | BP | E |
| M49467P07563K | 0.056 μF | 10% | BP | E |
| M49467R07563K | 0.056 μF | 10% | BR | B |
| M49467R07563M | 0.056 μF | 20% | BR | B |
| M49467P07683J | 0.068 μF | 5%  | BP | E |
| M49467P07683K | 0.068 μF | 10% | BP | E |
| M49467R07683K | 0.068 μF | 10% | BR | B |
| M49467R07683M | 0.068 μF | 20% | BR | B |
| M49467P07823K | 0.082 μF | 10% | BR | B |
| M49467R07823M | 0.082 μF | 20% | BR | B |
| M49467R07104K | 0.1 μF   | 10% | BR | C |
| M49467R07104M | 0.1 μF   | 20% | BR | C |
| M49467R07124K | 0.12 μF  | 10% | BR | D |
| M49467R07124M | 0.12 μF  | 20% | BR | D |
| M49467R07154K | 0.15 μF  | 10% | BR | D |
| M49467R07154M | 0.15 μF  | 20% | BR | D |
| M49467R07184K | 0.18 μF  | 10% | BR | D |
| M49467R07184M | 0.18 μF  | 20% | BR | D |
| M49467R07224K | 0.22 μF  | 10% | BR | D |
| M49467R07224M | 0.22 μF  | 20% | BR | D |
| M49467R07274K | 0.27 μF  | 10% | BR | D |
| M49467R07274M | 0.27 μF  | 20% | BR | D |
| M49467R07334K | 0.33 μF  | 10% | BR | E |
| M49467R07334M | 0.33 μF  | 20% | BR | E |
| M49467R07394K | 0.39 μF  | 10% | BR | E |
| M49467R07394M | 0.39 μF  | 20% | BR | E |
| M49467R07474K | 0.47 μF  | 10% | BR | E |
| M49467R07474M | 0.47 μF  | 20% | BR | E |

**CALL PRESIDIO FOR  
CROSS REFERENCE P/N'S**

### MIL-PRF-49467 PART NUMBER REFERENCE

**M49467**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



**PRESIDIO COMPONENTS, INC.**

7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

www.presidiocomponents.com • info@presidiocomponents.com

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 1000V

|               |        |     |    |   |
|---------------|--------|-----|----|---|
| M49467P01100J | 10 pF  | 5%  | BP | A |
| M49467P01100K | 10 pF  | 10% | BP | A |
| M49467P01120J | 12 pF  | 5%  | BP | A |
| M49467P01120K | 12 pF  | 10% | BP | A |
| M49467P01150J | 15 pF  | 5%  | BP | A |
| M49467P01150K | 15 pF  | 10% | BP | A |
| M49467P01180J | 18 pF  | 5%  | BP | A |
| M49467P01180K | 18 pF  | 10% | BP | A |
| M49467P01220J | 22 pF  | 5%  | BP | A |
| M49467P01220K | 22 pF  | 10% | BP | A |
| M49467P01270J | 27 pF  | 5%  | BP | A |
| M49467P01270K | 27 pF  | 10% | BP | A |
| M49467P01330J | 33 pF  | 5%  | BP | A |
| M49467P01330K | 33 pF  | 10% | BP | A |
| M49467P01390J | 39 pF  | 5%  | BP | A |
| M49467P01390K | 39 pF  | 10% | BP | A |
| M49467P01470J | 47 pF  | 5%  | BP | A |
| M49467P01470K | 47 pF  | 10% | BP | A |
| M49467P01560J | 56 pF  | 5%  | BP | A |
| M49467P01560K | 56 pF  | 10% | BP | A |
| M49467P01680J | 68 pF  | 5%  | BP | A |
| M49467P01680K | 68 pF  | 10% | BP | A |
| M49467P01820J | 82 pF  | 5%  | BP | A |
| M49467P01820K | 82 pF  | 10% | BP | A |
| M49467P01101J | 100 pF | 5%  | BP | A |
| M49467P01101K | 100 pF | 10% | BP | A |
| M49467R01101K | 100 pF | 10% | BR | A |
| M49467R01101M | 100 pF | 20% | BR | A |
| M49467P01121J | 120 pF | 5%  | BP | A |
| M49467P01121K | 120 pF | 10% | BP | A |
| M49467R01121K | 120 pF | 10% | BR | A |
| M49467R01121M | 120 pF | 20% | BR | A |
| M49467P01151J | 150 pF | 5%  | BP | A |
| M49467P01151K | 150 pF | 10% | BP | A |
| M49467R01151K | 150 pF | 10% | BR | A |
| M49467R01151M | 150 pF | 20% | BR | A |
| M49467P01181J | 180 pF | 5%  | BP | A |
| M49467R01181K | 180 pF | 10% | BP | A |
| M49467R01181M | 180 pF | 10% | BR | A |
| M49467R01181M | 180 pF | 20% | BR | A |
| M49467P01221J | 220 pF | 5%  | BP | A |
| M49467P01221K | 220 pF | 10% | BP | A |
| M49467R01221K | 220 pF | 10% | BR | A |
| M49467R01221M | 220 pF | 20% | BR | A |
| M49467P01271J | 270 pF | 5%  | BP | A |
| M49467P01271K | 270 pF | 10% | BP | A |
| M49467R01271K | 270 pF | 10% | BR | A |
| M49467R01271M | 270 pF | 20% | BR | A |
| M49467P01331J | 330 pF | 5%  | BP | A |
| M49467P01331K | 330 pF | 10% | BP | A |
| M49467R01331K | 330 pF | 10% | BR | A |
| M49467R01331M | 330 pF | 20% | BR | A |
| M49467P01391J | 390 pF | 5%  | BP | A |
| M49467P01391K | 390 pF | 10% | BP | A |
| M49467R01391K | 390 pF | 10% | BR | A |
| M49467R01391M | 390 pF | 20% | BR | A |
| M49467P01471J | 470 pF | 5%  | BP | A |
| M49467P01471K | 470 pF | 10% | BP | A |
| M49467R01471K | 470 pF | 10% | BR | A |
| M49467R01471M | 470 pF | 20% | BR | A |
| M49467P01561J | 560 pF | 5%  | BP | A |
| M49467P01561K | 560 pF | 10% | BP | A |
| M49467R01561K | 560 pF | 10% | BR | A |
| M49467R01561M | 560 pF | 20% | BR | A |
| M49467P01681J | 680 pF | 5%  | BP | A |
| M49467P01681K | 680 pF | 10% | BP | A |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 1000V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467R01681K | 680 pF   | 10% | BR | A |
| M49467R01681M | 680 pF   | 20% | BR | A |
| M49467P01821J | 820 pF   | 5%  | BP | A |
| M49467P01821K | 820 pF   | 10% | BP | A |
| M49467R01821K | 820 pF   | 10% | BR | A |
| M49467R01821M | 820 pF   | 20% | BR | A |
| M49467R01102K | 1000 pF  | 10% | BR | A |
| M49467R01102M | 1000 pF  | 20% | BR | A |
| M49467P01122J | 1200 pF  | 5%  | BP | B |
| M49467P01122K | 1200 pF  | 10% | BP | B |
| M49467R01122K | 1200 pF  | 10% | BR | A |
| M49467R01122M | 1200 pF  | 20% | BR | A |
| M49467P01152J | 1500 pF  | 5%  | BP | B |
| M49467P01152K | 1500 pF  | 10% | BP | B |
| M49467R01152K | 1500 pF  | 10% | BR | A |
| M49467R01152M | 1500 pF  | 20% | BR | A |
| M49467P01182J | 1800 pF  | 5%  | BP | B |
| M49467P01182K | 1800 pF  | 10% | BP | B |
| M49467R01182K | 1800 pF  | 10% | BR | A |
| M49467R01182M | 1800 pF  | 20% | BR | A |
| M49467P01222J | 2200 pF  | 5%  | BP | C |
| M49467P01222K | 2200 pF  | 10% | BP | C |
| M49467R01222K | 2200 pF  | 10% | BR | A |
| M49467R01222M | 2200 pF  | 20% | BR | A |
| M49467P01272J | 2700 pF  | 5%  | BP | C |
| M49467P01272K | 2700 pF  | 10% | BP | C |
| M49467R01272K | 2700 pF  | 10% | BR | A |
| M49467R01272M | 2700 pF  | 20% | BR | A |
| M49467R01332J | 3300 pF  | 5%  | BP | D |
| M49467P01332K | 3300 pF  | 10% | BP | D |
| M49467R01332K | 3300 pF  | 10% | BR | A |
| M49467R01332M | 3300 pF  | 20% | BR | A |
| M49467P01392J | 3900 pF  | 5%  | BP | D |
| M49467P01392K | 3900 pF  | 10% | BP | D |
| M49467R01392K | 3900 pF  | 10% | BR | A |
| M49467R01392M | 3900 pF  | 20% | BR | A |
| M49467P01472J | 4700 pF  | 5%  | BP | D |
| M49467R01472K | 4700 pF  | 10% | BP | D |
| M49467R01472K | 4700 pF  | 10% | BR | A |
| M49467R01472M | 4700 pF  | 20% | BR | A |
| M49467P01562J | 5600 pF  | 5%  | BP | E |
| M49467P01562K | 5600 pF  | 10% | BP | E |
| M49467R01562K | 5600 pF  | 10% | BR | B |
| M49467R01562M | 5600 pF  | 20% | BR | B |
| M49467Z01562K | 5600 pF  | 10% | BZ | A |
| M49467Z01562M | 5600 pF  | 20% | BZ | A |
| M49467P01682J | 6800 pF  | 5%  | BP | E |
| M49467P01682K | 6800 pF  | 10% | BP | E |
| M49467R01682K | 6800 pF  | 10% | BR | B |
| M49467R01682M | 6800 pF  | 20% | BR | B |
| M49467Z01682K | 6800 pF  | 10% | BZ | A |
| M49467Z01682M | 6800 pF  | 20% | BZ | A |
| M49467P01822J | 8200 pF  | 5%  | BP | E |
| M49467P01822K | 8200 pF  | 10% | BP | E |
| M49467R01822K | 8200 pF  | 10% | BR | B |
| M49467R01822M | 8200 pF  | 20% | BR | B |
| M49467Z01822K | 8200 pF  | 10% | BZ | A |
| M49467Z01822M | 8200 pF  | 20% | BZ | A |
| M49467P01103J | 0.01 μF  | 5%  | BP | E |
| M49467P01103K | 0.01 μF  | 10% | BP | E |
| M49467R01103K | 0.01 μF  | 10% | BR | B |
| M49467R01103M | 0.01 μF  | 20% | BR | B |
| M49467Z01103K | 0.01 μF  | 10% | BZ | A |
| M49467Z01103M | 0.01 μF  | 20% | BZ | A |
| M49467P01123J | 0.012 μF | 5%  | BP | F |
| M49467P01123K | 0.012 μF | 10% | BP | F |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 1000V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467R01123K | 0.012 μF | 10% | BR | C |
| M49467R01123M | 0.012 μF | 20% | BR | C |
| M49467Z01123K | 0.012 μF | 10% | BZ | B |
| M49467Z01123M | 0.012 μF | 20% | BZ | B |
| M49467P01153J | 0.015 μF | 5%  | BP | F |
| M49467P01153K | 0.015 μF | 10% | BP | F |
| M49467R01153K | 0.015 μF | 10% | BR | C |
| M49467R01153M | 0.015 μF | 20% | BR | C |
| M49467Z01153K | 0.015 μF | 10% | BZ | B |
| M49467Z01153M | 0.015 μF | 20% | BZ | B |
| M49467P01183J | 0.018 μF | 5%  | BP | F |
| M49467P01183K | 0.018 μF | 10% | BP | F |
| M49467R01183K | 0.018 μF | 10% | BR | D |
| M49467R01183M | 0.018 μF | 20% | BR | D |
| M49467Z01183K | 0.018 μF | 10% | BZ | B |
| M49467Z01183M | 0.018 μF | 20% | BZ | B |
| M49467P01223J | 0.022 μF | 5%  | BP | G |
| M49467P01223K | 0.022 μF | 10% | BP | G |
| M49467R01223K | 0.022 μF | 10% | BR | D |
| M49467R01223M | 0.022 μF | 20% | BR | D |
| M49467Z01223K | 0.022 μF | 10% | BZ | B |
| M49467Z01223M | 0.022 μF | 20% | BZ | B |
| M49467P01273J | 0.027 μF | 5%  | BP | G |
| M49467P01273K | 0.027 μF | 10% | BP | G |
| M49467R01273K | 0.027 μF | 10% | BR | C |
| M49467R01273M | 0.027 μF | 20% | BR | C |
| M49467R01333K | 0.033 μF | 10% | BR | D |
| M49467R01333M | 0.033 μF | 20% | BR | D |
| M49467R01393K | 0.039 μF | 10% | BR | D |
| M49467R01393M | 0.039 μF | 20% | BR | D |
| M49467R01473K | 0.047 μF | 10% | BR | D |
| M49467R01473M | 0.047 μF | 20% | BR | D |
| M49467Z01473K | 0.047 μF | 10% | BZ | D |
| M49467Z01473M | 0.047 μF | 20% | BZ | D |
| M49467R01563K | 0.056 μF | 10% | BR | D |
| M49467R01563M | 0.056 μF | 20% | BR | D |
| M49467Z01563K | 0.056 μF | 10% | BZ | D |
| M49467Z01563M | 0.056 μF | 20% | BZ | D |
| M49467R01683K | 0.068 μF | 10% | BR | D |
| M49467R01683M | 0.068 μF | 20% | BR | D |
| M49467R01823K | 0.082 μF | 10% | BR | E |
| M49467R01823M | 0.082 μF | 20% | BR | E |
| M49467R01104K | 0.1 μF   | 10% | BR | E |
| M49467R01104M | 0.1 μF   | 20% | BR | E |
| M49467R01124K | 0.12 μF  | 10% | BR | E |
| M49467R01124M | 0.12 μF  | 20% | BR | E |
| M49467Z01124K | 0.12 μF  | 10% | BZ | E |
| M49467Z01124M | 0.12 μF  | 20% | BZ | E |
| M49467R01154K | 0.15 μF  | 10% | BR | E |
| M49467R01154M | 0.15 μF  | 20% | BR | E |
| M49467R01184K | 0.18 μF  | 10% | BR | G |
| M49467R01184M | 0.18 μF  | 20% | BR | G |
| M49467Z01184K | 0.18 μF  | 10% | BZ | F |
| M49467Z01184M | 0.18 μF  | 20% | BZ | F |
| M49467R01224K | 0.22 μF  | 10% | BR | F |
| M49467R01224M | 0.22 μF  | 20% | BR | F |
| M49467R01274K | 0.27 μF  | 10% | BR | F |
| M49467R01274M | 0.27 μF  | 20% | BR | F |
| M49467R01334K | 0.33 μF  | 10% | BR | G |
| M49467R01334M | 0.33 μF  | 20% | BR | G |
| M49467R01394K | 0.39 μF  | 10% | BR | G |
| M49467R01394M | 0.39 μF  | 20% | BR | G |
| M49467R01474K | 0.47 μF  | 10% | BR | G |
| M49467R01474M | 0.47 μF  | 20% | BR | G |

### MIL-PRF-49467 PART NUMBER REFERENCE

**—**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>2000V</b>  |             |                |                |      |
| M49467P02100J | 10 pF       | 5%             | BP             | A    |
| M49467P02100K | 10 pF       | 10%            | BP             | A    |
| M49467P02120J | 12 pF       | 5%             | BP             | A    |
| M49467P02120K | 12 pF       | 10%            | BP             | A    |
| M49467P02150J | 15 pF       | 5%             | BP             | A    |
| M49467P02150K | 15 pF       | 10%            | BP             | A    |
| M49467P02180J | 18 pF       | 5%             | BP             | A    |
| M49467P02180K | 18 pF       | 10%            | BP             | A    |
| M49467P02220J | 22 pF       | 5%             | BP             | A    |
| M49467P02220K | 22 pF       | 10%            | BP             | A    |
| M49467P02270J | 27 pF       | 5%             | BP             | A    |
| M49467P02270K | 27 pF       | 10%            | BP             | A    |
| M49467P02330J | 33 pF       | 5%             | BP             | A    |
| M49467P02330K | 33 pF       | 10%            | BP             | A    |
| M49467P02390J | 39 pF       | 5%             | BP             | A    |
| M49467P02390K | 39 pF       | 10%            | BP             | A    |
| M49467P02470J | 47 pF       | 5%             | BP             | A    |
| M49467P02470K | 47 pF       | 10%            | BP             | A    |
| M49467P02560J | 56 pF       | 5%             | BP             | A    |
| M49467P02560K | 56 pF       | 10%            | BP             | A    |
| M49467P02680J | 68 pF       | 5%             | BP             | A    |
| M49467P02680K | 68 pF       | 10%            | BP             | A    |
| M49467P02820J | 82 pF       | 5%             | BP             | A    |
| M49467P02820K | 82 pF       | 10%            | BP             | A    |
| M49467P02101J | 100 pF      | 5%             | BP             | A    |
| M49467P02101K | 100 pF      | 10%            | BP             | A    |
| M49467R02101K | 100 pF      | 10%            | BR             | A    |
| M49467R02101M | 100 pF      | 20%            | BR             | A    |
| M49467P02121J | 120 pF      | 5%             | BP             | A    |
| M49467P02121K | 120 pF      | 10%            | BP             | A    |
| M49467R02121K | 120 pF      | 10%            | BR             | A    |
| M49467R02121M | 120 pF      | 20%            | BR             | A    |
| M49467P02151J | 150 pF      | 5%             | BP             | A    |
| M49467P02151K | 150 pF      | 10%            | BP             | A    |
| M49467R02151K | 150 pF      | 10%            | BR             | A    |
| M49467R02151M | 150 pF      | 20%            | BR             | A    |
| M49467P02181J | 180 pF      | 5%             | BP             | A    |
| M49467P02181K | 180 pF      | 10%            | BP             | A    |
| M49467R02181K | 180 pF      | 10%            | BR             | A    |
| M49467R02181M | 180 pF      | 20%            | BR             | A    |
| M49467P02221J | 220 pF      | 5%             | BP             | A    |
| M49467P02221K | 220 pF      | 10%            | BP             | A    |
| M49467R02221K | 220 pF      | 10%            | BR             | A    |
| M49467R02221M | 220 pF      | 20%            | BR             | A    |
| M49467P02271J | 270 pF      | 5%             | BP             | A    |
| M49467P02271K | 270 pF      | 10%            | BP             | A    |
| M49467R02271K | 270 pF      | 10%            | BR             | A    |
| M49467R02271M | 270 pF      | 20%            | BR             | A    |
| M49467P02331J | 330 pF      | 5%             | BP             | A    |
| M49467P02331K | 330 pF      | 10%            | BP             | A    |
| M49467R02331K | 330 pF      | 10%            | BR             | A    |
| M49467R02331M | 330 pF      | 20%            | BR             | A    |
| M49467P02391J | 390 pF      | 5%             | BP             | B    |
| M49467P02391K | 390 pF      | 10%            | BP             | B    |
| M49467R02391K | 390 pF      | 10%            | BR             | A    |
| M49467R02391M | 390 pF      | 20%            | BR             | A    |
| M49467P02471J | 470 pF      | 5%             | BP             | B    |
| M49467P02471K | 470 pF      | 10%            | BP             | B    |
| M49467R02471K | 470 pF      | 10%            | BR             | A    |
| M49467R02471M | 470 pF      | 20%            | BR             | A    |
| M49467P02561J | 560 pF      | 5%             | BP             | B    |
| M49467P02561K | 560 pF      | 10%            | BP             | B    |
| M49467R02561K | 560 pF      | 10%            | BR             | A    |
| M49467R02561M | 560 pF      | 20%            | BR             | A    |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>2000V</b>  |             |                |                |      |
| M49467P02681J | 680 pF      | 5%             | BP             | B    |
| M49467P02681K | 680 pF      | 10%            | BP             | B    |
| M49467R02681K | 680 pF      | 10%            | BR             | A    |
| M49467R02681M | 680 pF      | 20%            | BR             | A    |
| M49467P02821J | 820 pF      | 5%             | BP             | B    |
| M49467P02821K | 820 pF      | 10%            | BP             | B    |
| M49467R02821K | 820 pF      | 10%            | BR             | A    |
| M49467R02821M | 820 pF      | 20%            | BR             | A    |
| M49467P02102J | 1000 pF     | 5%             | BP             | C    |
| M49467P02102K | 1000 pF     | 10%            | BP             | C    |
| M49467R02102K | 1000 pF     | 10%            | BR             | A    |
| M49467R02102M | 1000 pF     | 20%            | BR             | A    |
| M49467P02122J | 1200 pF     | 5%             | BP             | C    |
| M49467P02122K | 1200 pF     | 10%            | BP             | C    |
| M49467R02122K | 1200 pF     | 10%            | BR             | A    |
| M49467R02122M | 1200 pF     | 20%            | BR             | A    |
| M49467P02152J | 1500 pF     | 5%             | BP             | D    |
| M49467P02152K | 1500 pF     | 10%            | BP             | D    |
| M49467R02152K | 1500 pF     | 10%            | BR             | A    |
| M49467R02152M | 1500 pF     | 20%            | BR             | A    |
| M49467P02182J | 1800 pF     | 5%             | BP             | D    |
| M49467P02182K | 1800 pF     | 10%            | BP             | D    |
| M49467R02182K | 1800 pF     | 10%            | BR             | B    |
| M49467R02182M | 1800 pF     | 20%            | BR             | B    |
| M49467Z02182K | 1800 pF     | 10%            | BZ             | A    |
| M49467Z02182M | 1800 pF     | 20%            | BZ             | A    |
| M49467P02222J | 2200 pF     | 5%             | BP             | D    |
| M49467P02222K | 2200 pF     | 10%            | BP             | D    |
| M49467R02222K | 2200 pF     | 10%            | BR             | B    |
| M49467R02222M | 2200 pF     | 20%            | BR             | B    |
| M49467Z02222K | 2200 pF     | 10%            | BZ             | A    |
| M49467Z02222M | 2200 pF     | 20%            | BZ             | A    |
| M49467P02272J | 2700 pF     | 5%             | BP             | E    |
| M49467P02272K | 2700 pF     | 10%            | BP             | E    |
| M49467R02272K | 2700 pF     | 10%            | BR             | B    |
| M49467R02272M | 2700 pF     | 20%            | BR             | B    |
| M49467Z02272K | 2700 pF     | 10%            | BZ             | A    |
| M49467Z02272M | 2700 pF     | 20%            | BZ             | A    |
| M49467P02332J | 3300 pF     | 5%             | BP             | E    |
| M49467P02332K | 3300 pF     | 10%            | BP             | E    |
| M49467R02332K | 3300 pF     | 10%            | BR             | B    |
| M49467R02332M | 3300 pF     | 20%            | BR             | B    |
| M49467P02392J | 3900 pF     | 5%             | BP             | E    |
| M49467P02392K | 3900 pF     | 10%            | BP             | E    |
| M49467R02392K | 3900 pF     | 10%            | BR             | B    |
| M49467R02392M | 3900 pF     | 20%            | BR             | B    |
| M49467P02472J | 4700 pF     | 5%             | BP             | E    |
| M49467P02472K | 4700 pF     | 10%            | BP             | E    |
| M49467R02472K | 4700 pF     | 10%            | BR             | C    |
| M49467R02472M | 4700 pF     | 20%            | BR             | C    |
| M49467Z02472K | 4700 pF     | 10%            | BZ             | B    |
| M49467Z02472M | 4700 pF     | 20%            | BZ             | B    |
| M49467P02562J | 5600 pF     | 5%             | BP             | F    |
| M49467P02562K | 5600 pF     | 10%            | BP             | F    |
| M49467R02562K | 5600 pF     | 10%            | BR             | C    |
| M49467R02562M | 5600 pF     | 20%            | BR             | C    |
| M49467Z02562K | 5600 pF     | 10%            | BZ             | B    |
| M49467Z02562M | 5600 pF     | 20%            | BZ             | B    |
| M49467P02682J | 6800 pF     | 5%             | BP             | F    |
| M49467P02682K | 6800 pF     | 10%            | BP             | F    |
| M49467R02682K | 6800 pF     | 10%            | BR             | D    |
| M49467R02682M | 6800 pF     | 20%            | BR             | D    |
| M49467Z02682K | 6800 pF     | 10%            | BZ             | B    |
| M49467Z02682M | 6800 pF     | 20%            | BZ             | B    |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>2000V</b>  |             |                |                |      |
| M49467P02822J | 8200 pF     | 5%             | BP             | G    |
| M49467P02822K | 8200 pF     | 10%            | BP             | G    |
| M49467R02822K | 8200 pF     | 10%            | BR             | D    |
| M49467R02822M | 8200 pF     | 20%            | BR             | D    |
| M49467Z02822K | 8200 pF     | 10%            | BZ             | C    |
| M49467Z02822M | 8200 pF     | 20%            | BZ             | C    |
| M49467P02103J | 0.01 μF     | 5%             | BP             | G    |
| M49467P02103K | 0.01 μF     | 10%            | BP             | G    |
| M49467R02103K | 0.01 μF     | 10%            | BR             | D    |
| M49467R02103M | 0.01 μF     | 20%            | BR             | D    |
| M49467Z02103K | 0.01 μF     | 10%            | BZ             | C    |
| M49467Z02103M | 0.01 μF     | 20%            | BZ             | C    |
| M49467R02123K | 0.012 μF    | 10%            | BR             | D    |
| M49467R02123M | 0.012 μF    | 20%            | BR             | D    |
| M49467R02153K | 0.015 μF    | 10%            | BR             | D    |
| M49467R02153M | 0.015 μF    | 20%            | BR             | D    |
| M49467R02183K | 0.018 μF    | 10%            | BR             | E    |
| M49467R02183M | 0.018 μF    | 20%            | BR             | E    |
| M49467Z02183K | 0.018 μF    | 10%            | BZ             | D    |
| M49467Z02183M | 0.018 μF    | 20%            | BZ             | D    |
| M49467R02223K | 0.022 μF    | 10%            | BR             | E    |
| M49467R02223M | 0.022 μF    | 20%            | BR             | E    |
| M49467Z02223K | 0.022 μF    | 10%            | BZ             | D    |
| M49467Z02223M | 0.022 μF    | 20%            | BZ             | D    |
| M49467R02273K | 0.027 μF    | 10%            | BR             | E    |
| M49467R02273M | 0.027 μF    | 20%            | BR             | E    |
| M49467Z02273K | 0.027 μF    | 10%            | BZ             | D    |
| M49467Z02273M | 0.027 μF    | 20%            | BZ             | D    |
| M49467R02333K | 0.033 μF    | 10%            | BR             | E    |
| M49467R02333M | 0.033 μF    | 20%            | BR             | E    |
| M49467R02393K | 0.039 μF    | 10%            | BR             | F    |
| M49467R02393M | 0.039 μF    | 20%            | BR             | F    |
| M49467Z02393K | 0.039 μF    | 10%            | BZ             | E    |
| M49467Z02393M | 0.039 μF    | 20%            | BZ             | E    |
| M49467R02473K | 0.047 μF    | 10%            | BR             | F    |
| M49467R02473M | 0.047 μF    | 20%            | BR             | F    |
| M49467Z02473K | 0.047 μF    | 10%            | BZ             | E    |
| M49467Z02473M | 0.047 μF    | 20%            | BZ             | E    |
| M49467R02563K | 0.056 μF    | 10%            | BR             | G    |
| M49467R02563M | 0.056 μF    | 20%            | BR             | G    |
| M49467Z02563K | 0.056 μF    | 10%            | BZ             | E    |
| M49467Z02563M | 0.056 μF    | 20%            | BZ             | E    |
| M49467R02683K | 0.068 μF    | 10%            | BR             | G    |
| M49467R02683M | 0.068 μF    | 20%            | BR             | G    |
| M49467Z02683K | 0.068 μF    | 10%            | BZ             | F    |
| M49467Z02683M | 0.068 μF    | 20%            | BZ             | F    |
| M49467R02823K | 0.082 μF    | 10%            | BR             | G    |
| M49467R02823M | 0.082 μF    | 20%            | BR             | G    |
| M49467Z02823K | 0.082 μF    | 10%            | BZ             | F    |
| M49467Z02823M | 0.082 μF    | 20%            | BZ             | F    |
| M49467R02104K | 0.1 μF      | 10%            | BR             | G    |
| M49467R02104M | 0.1 μF      | 20%            | BR             | G    |
| M49467Z02124K | 0.12 μF     | 10%            | BZ             | G    |
| M49467Z02124M | 0.12 μF     | 20%            | BZ             | G    |
| M49467Z02154K | 0.15 μF     | 10%            | BZ             | G    |
| M49467Z02154M | 0.15 μF     | 20%            | BZ             | G    |

**CALL PRESIDIO FOR  
CROSS REFERENCE P/N'S**

## MIL-PRF-49467 PART NUMBER REFERENCE

**M49467**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



**PRESIDIO COMPONENTS, INC.**

7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

www.presidiocomponents.com • info@presidiocomponents.com

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 3000V

|               |        |     |    |   |
|---------------|--------|-----|----|---|
| M49467P03100J | 10 pF  | 5%  | BP | B |
| M49467P03100K | 10 pF  | 10% | BP | B |
| M49467P03120J | 12 pF  | 5%  | BP | B |
| M49467P03120K | 12 pF  | 10% | BP | B |
| M49467P03150J | 15 pF  | 5%  | BP | B |
| M49467P03150K | 15 pF  | 10% | BP | B |
| M49467P03180J | 18 pF  | 5%  | BP | B |
| M49467P03180K | 18 pF  | 10% | BP | B |
| M49467P03220J | 22 pF  | 5%  | BP | B |
| M49467P03220K | 22 pF  | 10% | BP | B |
| M49467P03270J | 27 pF  | 5%  | BP | B |
| M49467P03270K | 27 pF  | 10% | BP | B |
| M49467P03330J | 33 pF  | 5%  | BP | B |
| M49467P03330K | 33 pF  | 10% | BP | B |
| M49467P03390J | 39 pF  | 5%  | BP | B |
| M49467P03390K | 39 pF  | 10% | BP | B |
| M49467P03470J | 47 pF  | 5%  | BP | B |
| M49467P03470K | 47 pF  | 10% | BP | B |
| M49467P03560J | 56 pF  | 5%  | BP | B |
| M49467P03560K | 56 pF  | 10% | BP | B |
| M49467P03680J | 68 pF  | 5%  | BP | B |
| M49467P03680K | 68 pF  | 10% | BP | B |
| M49467P03820J | 82 pF  | 5%  | BP | B |
| M49467P03820K | 82 pF  | 10% | BP | B |
| M49467P03101J | 100 pF | 5%  | BP | B |
| M49467P03101K | 100 pF | 10% | BP | B |
| M49467R03101K | 100 pF | 10% | BR | B |
| M49467R03101M | 100 pF | 20% | BR | B |
| M49467P03121J | 120 pF | 5%  | BP | B |
| M49467P03121K | 120 pF | 10% | BP | B |
| M49467R03121K | 120 pF | 10% | BR | B |
| M49467R03121M | 120 pF | 20% | BR | B |
| M49467P03151J | 150 pF | 5%  | BP | B |
| M49467P03151K | 150 pF | 10% | BP | B |
| M49467R03151K | 150 pF | 10% | BR | B |
| M49467R03151M | 150 pF | 20% | BR | B |
| M49467P03181J | 180 pF | 5%  | BP | B |
| M49467P03181K | 180 pF | 10% | BP | B |
| M49467R03181M | 180 pF | 20% | BR | B |
| M49467P03221J | 220 pF | 5%  | BP | B |
| M49467P03221K | 220 pF | 10% | BP | B |
| M49467R03221K | 220 pF | 10% | BR | B |
| M49467R03221M | 220 pF | 20% | BR | B |
| M49467P03271J | 270 pF | 5%  | BP | B |
| M49467P03271K | 270 pF | 10% | BP | B |
| M49467R03271K | 270 pF | 10% | BR | B |
| M49467R03271M | 270 pF | 20% | BR | B |
| M49467P03331J | 330 pF | 5%  | BP | B |
| M49467P03331K | 330 pF | 10% | BP | B |
| M49467R03331K | 330 pF | 10% | BR | B |
| M49467R03331M | 330 pF | 20% | BR | B |
| M49467P03391J | 390 pF | 5%  | BP | B |
| M49467P03391K | 390 pF | 10% | BP | B |
| M49467R03391K | 390 pF | 10% | BR | B |
| M49467R03391M | 390 pF | 20% | BR | B |
| M49467P03471J | 470 pF | 5%  | BP | B |
| M49467P03471K | 470 pF | 10% | BP | B |
| M49467R03471K | 470 pF | 10% | BR | B |
| M49467R03471M | 470 pF | 20% | BR | B |
| M49467P03561J | 560 pF | 5%  | BP | B |
| M49467P03561K | 560 pF | 10% | BP | B |
| M49467R03561K | 560 pF | 10% | BR | B |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 3000V

|               |         |     |    |   |
|---------------|---------|-----|----|---|
| M49467R03561M | 560 pF  | 20% | BR | B |
| M49467P0368J  | 680 pF  | 5%  | BP | C |
| M49467P03681K | 680 pF  | 10% | BP | C |
| M49467R03681K | 680 pF  | 10% | BR | B |
| M49467R03681M | 680 pF  | 20% | BR | B |
| M49467P03821J | 820 pF  | 5%  | BP | D |
| M49467P03821K | 820 pF  | 10% | BP | D |
| M49467R03821K | 820 pF  | 10% | BR | B |
| M49467R03821M | 820 pF  | 20% | BR | B |
| M49467P03102J | 1000 pF | 5%  | BP | D |
| M49467P03102K | 1000 pF | 10% | BP | D |
| M49467R03102M | 1000 pF | 20% | BR | B |
| M49467P03122J | 1200 pF | 5%  | BP | D |
| M49467P03122K | 1200 pF | 10% | BP | D |
| M49467R03122K | 1200 pF | 10% | BR | B |
| M49467R03122M | 1200 pF | 20% | BR | B |
| M49467P03152J | 1500 pF | 5%  | BP | D |
| M49467P03152K | 1500 pF | 10% | BP | D |
| M49467R03152K | 1500 pF | 10% | BR | B |
| M49467R03152M | 1500 pF | 20% | BR | B |
| M49467P03182J | 1800 pF | 5%  | BP | E |
| M49467P03182K | 1800 pF | 10% | BP | E |
| M49467R03182K | 1800 pF | 10% | BR | C |
| M49467R03182M | 1800 pF | 20% | BR | C |
| M49467Z03182J | 1800 pF | 10% | BZ | B |
| M49467Z03182K | 1800 pF | 20% | BZ | B |
| M49467P03222J | 2200 pF | 5%  | BP | E |
| M49467P03222K | 2200 pF | 10% | BP | E |
| M49467R03222K | 2200 pF | 10% | BR | C |
| M49467R03222M | 2200 pF | 20% | BR | C |
| M49467Z03222K | 2200 pF | 10% | BZ | B |
| M49467Z03222M | 2200 pF | 20% | BZ | B |
| M49467P03272J | 2700 pF | 5%  | BP | E |
| M49467P03272K | 2700 pF | 10% | BP | E |
| M49467R03272K | 2700 pF | 10% | BR | D |
| M49467R03272M | 2700 pF | 20% | BR | D |
| M49467Z03272K | 2700 pF | 10% | BZ | C |
| M49467P03332J | 3300 pF | 5%  | BP | E |
| M49467P03332K | 3300 pF | 10% | BP | E |
| M49467R03332M | 3300 pF | 20% | BR | D |
| M49467Z03332K | 3300 pF | 10% | BZ | C |
| M49467Z03332M | 3300 pF | 20% | BZ | C |
| M49467P03392J | 3900 pF | 5%  | BP | F |
| M49467P03392K | 3900 pF | 10% | BP | F |
| M49467R03392K | 3900 pF | 10% | BR | D |
| M49467R03392M | 3900 pF | 20% | BR | D |
| M49467Z03392K | 3900 pF | 10% | BZ | C |
| M49467Z03392M | 3900 pF | 20% | BZ | C |
| M49467P03472J | 4700 pF | 5%  | BP | F |
| M49467P03472K | 4700 pF | 10% | BP | F |
| M49467R03472K | 4700 pF | 10% | BR | D |
| M49467R03472M | 4700 pF | 20% | BR | D |
| M49467P03562J | 5600 pF | 5%  | BP | F |
| M49467P03562K | 5600 pF | 10% | BP | F |
| M49467R03562M | 5600 pF | 20% | BR | D |
| M49467P03682J | 6800 pF | 5%  | BP | G |
| M49467P03682K | 6800 pF | 10% | BP | G |
| M49467R03682K | 6800 pF | 10% | BR | D |
| M49467R03682M | 6800 pF | 20% | BR | D |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 3000V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467R03822K | 8200 pF  | 10% | BR | E |
| M49467R03822M | 8200 pF  | 20% | BR | E |
| M49467Z03822K | 8200 pF  | 10% | BZ | D |
| M49467Z03822M | 8200 pF  | 20% | BZ | D |
| M49467R03103K | 0.01 μF  | 10% | BR | E |
| M49467R03103M | 0.01 μF  | 20% | BR | E |
| M49467Z03103K | 0.01 μF  | 10% | BZ | D |
| M49467Z03103M | 0.01 μF  | 20% | BZ | D |
| M49467R03123K | 0.012 μF | 10% | BR | E |
| M49467R03123M | 0.012 μF | 20% | BR | E |
| M49467Z03123K | 0.012 μF | 10% | BZ | D |
| M49467Z03123M | 0.012 μF | 20% | BZ | D |
| M49467R03153K | 0.015 μF | 10% | BR | F |
| M49467R03153M | 0.015 μF | 20% | BR | F |
| M49467Z03153K | 0.015 μF | 10% | BZ | E |
| M49467Z03153M | 0.015 μF | 20% | BZ | E |
| M49467R03183K | 0.018 μF | 10% | BR | F |
| M49467R03183M | 0.018 μF | 20% | BR | F |
| M49467Z03183K | 0.018 μF | 10% | BZ | E |
| M49467Z03183M | 0.018 μF | 20% | BZ | E |
| M49467R03223K | 0.022 μF | 10% | BR | F |
| M49467R03223M | 0.022 μF | 20% | BR | F |
| M49467Z03223K | 0.022 μF | 10% | BZ | E |
| M49467Z03223M | 0.022 μF | 20% | BZ | E |
| M49467R03273K | 0.027 μF | 10% | BR | G |
| M49467R03273M | 0.027 μF | 20% | BR | G |
| M49467Z03273K | 0.027 μF | 10% | BZ | F |
| M49467Z03273M | 0.027 μF | 20% | BZ | F |
| M49467R03333K | 0.033 μF | 10% | BR | G |
| M49467R03333M | 0.033 μF | 20% | BR | G |
| M49467Z03333K | 0.033 μF | 10% | BZ | F |
| M49467Z03333M | 0.033 μF | 20% | BZ | F |
| M49467R03393K | 0.039 μF | 10% | BR | G |
| M49467R03393M | 0.039 μF | 20% | BR | G |
| M49467R03473K | 0.047 μF | 10% | BR | J |
| M49467R03473M | 0.047 μF | 20% | BR | J |
| M49467Z03473K | 0.047 μF | 10% | BZ | G |
| M49467Z03473M | 0.047 μF | 20% | BZ | G |
| M49467R03563K | 0.056 μF | 10% | BR | K |
| M49467R03563M | 0.056 μF | 20% | BR | K |
| M49467Z03563K | 0.056 μF | 10% | BZ | G |
| M49467Z03563M | 0.056 μF | 20% | BZ | G |
| M49467R03683K | 0.068 μF | 10% | BR | K |
| M49467R03683M | 0.068 μF | 20% | BR | K |
| M49467Z03683K | 0.068 μF | 10% | BZ | J |
| M49467Z03683M | 0.068 μF | 20% | BZ | J |
| M49467R03823K | 0.082 μF | 10% | BR | K |
| M49467R03823M | 0.082 μF | 20% | BR | K |
| M49467R03104K | 0.1 μF   | 10% | BR | K |
| M49467R03104M | 0.1 μF   | 20% | BR | K |

**CALL PRESIDIO FOR  
CROSS REFERENCE P/N'S**

### MIL-PRF-49467 PART NUMBER REFERENCE

**M49467**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



**PRESIDIO COMPONENTS, INC.**

7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

www.presidiocomponents.com • info@presidiocomponents.com

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>4000V</b>  |             |                |                |      |
| M49467P04100J | 10 pF       | 5%             | BP             | L    |
| M49467P04100K | 10 pF       | 10%            | BP             | L    |
| M49467P04120J | 12 pF       | 5%             | BP             | L    |
| M49467P04120K | 12 pF       | 10%            | BP             | L    |
| M49467P04150J | 15 pF       | 5%             | BP             | L    |
| M49467P04150K | 15 pF       | 10%            | BP             | L    |
| M49467P04180J | 18 pF       | 5%             | BP             | L    |
| M49467P04180K | 18 pF       | 10%            | BP             | L    |
| M49467P04220J | 22 pF       | 5%             | BP             | L    |
| M49467P04220K | 22 pF       | 10%            | BP             | L    |
| M49467P04270J | 27 pF       | 5%             | BP             | L    |
| M49467P04270K | 27 pF       | 10%            | BP             | L    |
| M49467P04330J | 33 pF       | 5%             | BP             | L    |
| M49467P04330K | 33 pF       | 10%            | BP             | L    |
| M49467P04390J | 39 pF       | 5%             | BP             | L    |
| M49467P04390K | 39 pF       | 10%            | BP             | L    |
| M49467P04470J | 47 pF       | 5%             | BP             | L    |
| M49467P04470K | 47 pF       | 10%            | BP             | L    |
| M49467P04560J | 56 pF       | 5%             | BP             | L    |
| M49467P04560K | 56 pF       | 10%            | BP             | L    |
| M49467P04680J | 68 pF       | 5%             | BP             | L    |
| M49467P04680K | 68 pF       | 10%            | BP             | L    |
| M49467P04820J | 82 pF       | 5%             | BP             | L    |
| M49467P04820K | 82 pF       | 10%            | BP             | L    |
| M49467P04101J | 100 pF      | 5%             | BP             | D    |
| M49467P04101K | 100 pF      | 10%            | BP             | D    |
| M49467R04101K | 100 pF      | 10%            | BR             | M    |
| M49467R04101M | 100 pF      | 20%            | BR             | M    |
| M49467P04121J | 120 pF      | 5%             | BP             | D    |
| M49467P04121K | 120 pF      | 10%            | BP             | D    |
| M49467R04121M | 120 pF      | 20%            | BR             | M    |
| M49467P04151J | 150 pF      | 5%             | BP             | D    |
| M49467P04151K | 150 pF      | 10%            | BP             | D    |
| M49467R04151K | 150 pF      | 10%            | BR             | M    |
| M49467R04151M | 150 pF      | 20%            | BR             | M    |
| M49467P04181J | 180 pF      | 5%             | BP             | D    |
| M49467P04181K | 180 pF      | 10%            | BP             | D    |
| M49467R04181K | 180 pF      | 10%            | BR             | M    |
| M49467R04181M | 180 pF      | 20%            | BR             | M    |
| M49467P04221J | 220 pF      | 5%             | BP             | D    |
| M49467P04221K | 220 pF      | 10%            | BP             | D    |
| M49467R04221M | 220 pF      | 20%            | BR             | M    |
| M49467P04271J | 270 pF      | 5%             | BP             | D    |
| M49467P04271K | 270 pF      | 10%            | BP             | D    |
| M49467R04271M | 270 pF      | 20%            | BR             | M    |
| M49467P04331J | 330 pF      | 5%             | BP             | D    |
| M49467P04331K | 330 pF      | 10%            | BP             | D    |
| M49467R04331K | 330 pF      | 10%            | BR             | M    |
| M49467R04331M | 330 pF      | 20%            | BR             | M    |
| M49467P04391J | 390 pF      | 5%             | BP             | D    |
| M49467P04391K | 390 pF      | 10%            | BP             | D    |
| M49467R04391K | 390 pF      | 10%            | BR             | M    |
| M49467R04391M | 390 pF      | 20%            | BR             | M    |
| M49467P04471J | 470 pF      | 5%             | BP             | D    |
| M49467P04471K | 470 pF      | 10%            | BP             | D    |
| M49467R04471K | 470 pF      | 10%            | BR             | M    |
| M49467R04471M | 470 pF      | 20%            | BR             | M    |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>4000V</b>  |             |                |                |      |
| M49467P04561J | 560 pF      | 5%             | BP             | D    |
| M49467P04561K | 560 pF      | 10%            | BP             | D    |
| M49467R04561K | 560 pF      | 10%            | BR             | M    |
| M49467R04561M | 560 pF      | 20%            | BR             | M    |
| M49467P04681J | 680 pF      | 5%             | BP             | D    |
| M49467P04681K | 680 pF      | 10%            | BP             | D    |
| M49467R04681K | 680 pF      | 10%            | BR             | M    |
| M49467R04681M | 680 pF      | 20%            | BR             | M    |
| M49467P04821J | 820 pF      | 5%             | BP             | D    |
| M49467P04821K | 820 pF      | 10%            | BP             | D    |
| M49467R04821K | 820 pF      | 10%            | BR             | M    |
| M49467R04821M | 820 pF      | 20%            | BR             | M    |
| M49467P04102J | 1000 pF     | 5%             | BP             | D    |
| M49467P04102K | 1000 pF     | 10%            | BP             | D    |
| M49467R04102K | 1000 pF     | 10%            | BR             | D    |
| M49467R04101M | 1000 pF     | 20%            | BR             | D    |
| M49467P04122J | 1200 pF     | 5%             | BP             | E    |
| M49467P04122K | 1200 pF     | 10%            | BP             | E    |
| M49467R04122M | 1200 pF     | 20%            | BR             | D    |
| M49467P04152J | 1500 pF     | 5%             | BP             | E    |
| M49467P04152K | 1500 pF     | 10%            | BP             | E    |
| M49467R04152K | 1500 pF     | 10%            | BR             | D    |
| M49467R04152M | 1500 pF     | 20%            | BR             | D    |
| M49467P04182J | 1800 pF     | 5%             | BP             | E    |
| M49467P04182K | 1800 pF     | 10%            | BP             | E    |
| M49467R04182K | 1800 pF     | 10%            | BR             | D    |
| M49467R04182M | 1800 pF     | 20%            | BR             | D    |
| M49467P04222J | 2200 pF     | 5%             | BP             | F    |
| M49467P04222K | 2200 pF     | 10%            | BP             | F    |
| M49467R04222M | 2200 pF     | 20%            | BR             | D    |
| M49467P04272J | 2700 pF     | 5%             | BP             | F    |
| M49467P04272K | 2700 pF     | 10%            | BP             | F    |
| M49467R04272K | 2700 pF     | 10%            | BR             | D    |
| M49467R04272M | 2700 pF     | 20%            | BR             | D    |
| M49467P04332J | 3300 pF     | 5%             | BP             | G    |
| M49467P04332K | 3300 pF     | 10%            | BP             | G    |
| M49467R04332K | 3300 pF     | 10%            | BR             | D    |
| M49467R04332M | 3300 pF     | 20%            | BR             | D    |
| M49467P04392K | 3900 pF     | 10%            | BP             | G    |
| M49467R04392K | 3900 pF     | 10%            | BR             | D    |
| M49467R04392M | 3900 pF     | 20%            | BR             | D    |
| M49467P04472J | 4700 pF     | 5%             | BP             | K    |
| M49467P04472K | 4700 pF     | 10%            | BP             | K    |
| M49467R04472K | 4700 pF     | 10%            | BR             | E    |
| M49467R04472M | 4700 pF     | 20%            | BR             | E    |
| M49467P04562K | 5600 pF     | 10%            | BP             | K    |
| M49467P04562M | 5600 pF     | 20%            | BP             | K    |
| M49467R04562K | 5600 pF     | 10%            | BR             | E    |
| M49467R04562M | 5600 pF     | 20%            | BR             | E    |
| M49467Z04562K | 5600 pF     | 10%            | BZ             | D    |
| M49467Z04562M | 5600 pF     | 20%            | BZ             | D    |
| M49467P04682K | 6800 pF     | 10%            | BP             | K    |
| M49467P04682M | 6800 pF     | 20%            | BP             | K    |
| M49467R04682K | 6800 pF     | 10%            | BR             | E    |
| M49467R04682M | 6800 pF     | 20%            | BR             | E    |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
| <b>4000V</b>  |             |                |                |      |
| M49467Z04682K | 6800 pF     | 10%            | BZ             | D    |
| M49467Z04682M | 6800 pF     | 20%            | BZ             | D    |
| M49467R04822K | 8200 pF     | 10%            | BR             | F    |
| M49467R04822M | 8200 pF     | 20%            | BR             | F    |
| M49467Z04822K | 8200 pF     | 10%            | BZ             | E    |
| M49467Z04822M | 8200 pF     | 20%            | BZ             | E    |
| M49467R04103K | 0.01 μF     | 10%            | BR             | F    |
| M49467R04103M | 0.01 μF     | 20%            | BR             | F    |
| M49467Z04103K | 0.01 μF     | 10%            | BZ             | E    |
| M49467Z04103M | 0.01 μF     | 20%            | BZ             | E    |
| M49467R04123K | 0.012 μF    | 10%            | BR             | G    |
| M49467R04123M | 0.012 μF    | 20%            | BR             | G    |
| M49467Z04123K | 0.012 μF    | 10%            | BZ             | F    |
| M49467Z04123M | 0.012 μF    | 20%            | BZ             | F    |
| M49467R04153K | 0.015 μF    | 10%            | BR             | G    |
| M49467R04153M | 0.015 μF    | 20%            | BR             | G    |
| M49467Z04153K | 0.015 μF    | 10%            | BZ             | F    |
| M49467Z04153M | 0.015 μF    | 20%            | BZ             | F    |
| M49467R04183K | 0.018 μF    | 10%            | BR             | G    |
| M49467R04183M | 0.018 μF    | 20%            | BR             | G    |
| M49467R04223K | 0.022 μF    | 10%            | BR             | J    |
| M49467R04223M | 0.022 μF    | 20%            | BR             | J    |
| M49467Z04223K | 0.022 μF    | 10%            | BZ             | G    |
| M49467Z04223M | 0.022 μF    | 20%            | BZ             | G    |
| M49467R04273K | 0.027 μF    | 10%            | BR             | J    |
| M49467R04273M | 0.027 μF    | 20%            | BR             | J    |
| M49467Z04273K | 0.027 μF    | 10%            | BZ             | G    |
| M49467Z04273M | 0.027 μF    | 20%            | BZ             | G    |
| M49467R04333K | 0.033 μF    | 10%            | BR             | K    |
| M49467R04333M | 0.033 μF    | 20%            | BR             | K    |
| M49467Z04333K | 0.033 μF    | 10%            | BZ             | J    |
| M49467Z04333M | 0.033 μF    | 20%            | BZ             | J    |
| M49467R04393K | 0.039 μF    | 10%            | BR             | K    |
| M49467R04393M | 0.039 μF    | 20%            | BR             | K    |
| M49467Z04393K | 0.039 μF    | 10%            | BZ             | J    |
| M49467Z04393M | 0.039 μF    | 20%            | BZ             | J    |
| M49467R04473K | 0.047 μF    | 10%            | BR             | K    |
| M49467R04473M | 0.047 μF    | 20%            | BR             | K    |
| M49467Z04473K | 0.047 μF    | 10%            | BZ             | K    |
| M49467Z04473M | 0.047 μF    | 20%            | BZ             | K    |
| M49467R04563K | 0.056 μF    | 10%            | BR             | K    |
| M49467R04563M | 0.056 μF    | 20%            | BR             | K    |

**CALL PRESIDIO FOR  
CROSS REFERENCE P/N'S**

## MIL-PRF-49467 PART NUMBER REFERENCE

**M49467**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



**PRESIDIO COMPONENTS, INC.**

7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

www.presidiocomponents.com • info@presidiocomponents.com

# MIL-PRF-49467 STANDARD PROFILE

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 5000V

|               |        |     |    |   |
|---------------|--------|-----|----|---|
| M49467P05100J | 10 pF  | 5%  | BP | M |
| M49467P05100K | 10 pF  | 10% | BP | M |
| M49467P05120J | 12 pF  | 5%  | BP | M |
| M49467P05120K | 12 pF  | 10% | BP | M |
| M49467P05150J | 15 pF  | 5%  | BP | M |
| M49467P05150K | 15 pF  | 10% | BP | M |
| M49467P05180J | 18 pF  | 5%  | BP | M |
| M49467P05180K | 18 pF  | 10% | BP | M |
| M49467P05220J | 22 pF  | 5%  | BP | M |
| M49467P05220K | 22 pF  | 10% | BP | M |
| M49467P05270J | 27 pF  | 5%  | BP | M |
| M49467P05270K | 27 pF  | 10% | BP | M |
| M49467P05330J | 33 pF  | 5%  | BP | M |
| M49467P05330K | 33 pF  | 10% | BP | M |
| M49467P05390J | 39 pF  | 5%  | BP | M |
| M49467P05390K | 39 pF  | 10% | BP | M |
| M49467P05470J | 47 pF  | 5%  | BP | M |
| M49467P05470K | 47 pF  | 10% | BP | M |
| M49467P05560J | 56 pF  | 5%  | BP | M |
| M49467P05560K | 56 pF  | 10% | BP | M |
| M49467P05680J | 68 pF  | 5%  | BP | M |
| M49467P05680K | 68 pF  | 10% | BP | M |
| M49467P05820J | 82 pF  | 5%  | BP | M |
| M49467P05820K | 82 pF  | 10% | BP | M |
| M49467P05101J | 100 pF | 5%  | BP | M |
| M49467P05101K | 100 pF | 10% | BP | M |
| M49467R05101J | 100 pF | 5%  | BR | M |
| M49467R05101K | 100 pF | 10% | BR | M |
| M49467P05121J | 120 pF | 5%  | BP | M |
| M49467P05121K | 120 pF | 10% | BP | M |
| M49467R05121J | 120 pF | 5%  | BR | M |
| M49467R05121K | 120 pF | 10% | BR | M |
| M49467P05151J | 150 pF | 5%  | BP | M |
| M49467P05151K | 150 pF | 10% | BP | M |
| M49467R05151K | 150 pF | 10% | BR | M |
| M49467R05151M | 150 pF | 20% | BR | M |
| M49467P05181J | 180 pF | 5%  | BP | M |
| M49467P05181K | 180 pF | 10% | BP | M |
| M49467R05181K | 180 pF | 10% | BR | M |
| M49467R05181M | 180 pF | 20% | BR | M |
| M49467P05221J | 220 pF | 5%  | BP | M |
| M49467P05221K | 220 pF | 10% | BP | M |
| M49467R05221K | 220 pF | 10% | BR | M |
| M49467R05221M | 220 pF | 20% | BR | M |
| M49467P05271J | 270 pF | 5%  | BP | M |
| M49467P05271K | 270 pF | 10% | BP | M |
| M49467R05271K | 270 pF | 10% | BR | M |
| M49467R05271M | 270 pF | 20% | BR | M |
| M49467P05331J | 330 pF | 5%  | BP | E |
| M49467P05331K | 330 pF | 10% | BP | E |
| M49467R05331K | 330 pF | 10% | BR | M |
| M49467R05331M | 330 pF | 20% | BR | M |
| M49467P05391J | 390 pF | 5%  | BP | E |
| M49467P05391K | 390 pF | 10% | BP | E |
| M49467R05391K | 390 pF | 10% | BR | M |
| M49467R05391M | 390 pF | 20% | BR | M |
| M49467P05471J | 470 pF | 5%  | BP | F |
| M49467P05471K | 470 pF | 10% | BP | F |
| M49467R05471K | 470 pF | 10% | BR | M |
| M49467R05471M | 470 pF | 20% | BR | M |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 5000V

|               |         |     |    |   |
|---------------|---------|-----|----|---|
| M49467P05561J | 560 pF  | 5%  | BP | F |
| M49467P05561K | 560 pF  | 10% | BP | F |
| M49467R05561K | 560 pF  | 10% | BR | M |
| M49467R05561M | 560 pF  | 20% | BR | M |
| M49467P05681J | 680 pF  | 5%  | BP | F |
| M49467P05681K | 680 pF  | 10% | BP | F |
| M49467R05681K | 680 pF  | 10% | BR | E |
| M49467R05681M | 680 pF  | 20% | BR | E |
| M49467P05821J | 820 pF  | 5%  | BP | F |
| M49467P05821K | 820 pF  | 10% | BP | F |
| M49467R05821K | 820 pF  | 10% | BR | E |
| M49467R05821M | 820 pF  | 20% | BR | E |
| M49467P05102J | 1000 pF | 5%  | BP | F |
| M49467P05102K | 1000 pF | 10% | BP | F |
| M49467R05102K | 1000 pF | 10% | BR | E |
| M49467R05102M | 1000 pF | 20% | BR | E |
| M49467P05122J | 1200 pF | 5%  | BP | F |
| M49467P05122K | 1200 pF | 10% | BP | F |
| M49467R05122K | 1200 pF | 10% | BR | E |
| M49467R05122M | 1200 pF | 20% | BR | E |
| M49467P05152J | 1500 pF | 5%  | BP | F |
| M49467P05152K | 1500 pF | 10% | BP | F |
| M49467R05152K | 1500 pF | 10% | BR | E |
| M49467R05152M | 1500 pF | 20% | BR | E |
| M49467P05182J | 1800 pF | 5%  | BP | F |
| M49467P05182K | 1800 pF | 10% | BP | F |
| M49467R05182K | 1800 pF | 10% | BR | E |
| M49467R05182M | 1800 pF | 20% | BR | E |
| M49467P05222J | 2200 pF | 5%  | BP | G |
| M49467P05222K | 2200 pF | 10% | BP | G |
| M49467R05222K | 2200 pF | 10% | BR | E |
| M49467R05222M | 2200 pF | 20% | BR | E |
| M49467P05272J | 2700 pF | 5%  | BP | G |
| M49467P05272K | 2700 pF | 10% | BP | G |
| M49467R05272K | 2700 pF | 10% | BR | F |
| M49467R05272M | 2700 pF | 20% | BR | F |
| M49467Z05272K | 2700 pF | 10% | BZ | E |
| M49467Z05272M | 2700 pF | 20% | BZ | E |
| M49467P05332J | 3300 pF | 5%  | BP | G |
| M49467P05332K | 3300 pF | 10% | BP | G |
| M49467R05332K | 3300 pF | 10% | BR | F |
| M49467R05332M | 3300 pF | 20% | BR | F |
| M49467Z05332K | 3300 pF | 10% | BZ | E |
| M49467Z05332M | 3300 pF | 20% | BZ | E |
| M49467P05392J | 3900 pF | 5%  | BP | K |
| M49467P05392K | 3900 pF | 10% | BP | K |
| M49467R05392K | 3900 pF | 10% | BR | F |
| M49467R05392M | 3900 pF | 20% | BR | F |
| M49467Z05392K | 3900 pF | 10% | BZ | E |
| M49467Z05392M | 3900 pF | 20% | BZ | E |
| M49467P05472J | 4700 pF | 5%  | BP | K |
| M49467P05472K | 4700 pF | 10% | BP | K |
| M49467R05472K | 4700 pF | 10% | BR | F |
| M49467R05472M | 4700 pF | 20% | BR | F |
| M49467Z05472K | 4700 pF | 10% | BZ | E |
| M49467Z05472M | 4700 pF | 20% | BZ | E |
| M49467R05562J | 5600 pF | 5%  | BP | K |
| M49467R05562K | 5600 pF | 10% | BP | K |
| M49467R05562M | 5600 pF | 10% | BR | F |
| M49467R05562M | 5600 pF | 20% | BR | F |

| MIL-PRF-49467 | Capacitance | Cap. Tolerance | Characteristic | Case |
|---------------|-------------|----------------|----------------|------|
|---------------|-------------|----------------|----------------|------|

## 5000V

|               |          |     |    |   |
|---------------|----------|-----|----|---|
| M49467Z05562K | 5600 pF  | 10% | BZ | F |
| M49467Z05562M | 5600 pF  | 20% | BZ | F |
| M49467R0568K  | 6800 pF  | 10% | BR | G |
| M49467R05682M | 6800 pF  | 20% | BR | G |
| M49467Z05682K | 6800 pF  | 10% | BZ | F |
| M49467Z05682M | 6800 pF  | 20% | BZ | F |
| M49467R05822K | 8200 pF  | 10% | BR | G |
| M49467R05822M | 8200 pF  | 20% | BR | G |
| M49467Z05822K | 8200 pF  | 10% | BZ | G |
| M49467Z05822M | 8200 pF  | 20% | BZ | G |
| M49467R05103K | 0.01 μF  | 10% | BR | J |
| M49467R05103M | 0.01 μF  | 20% | BR | J |
| M49467Z05103K | 0.01 μF  | 10% | BZ | G |
| M49467Z05103M | 0.01 μF  | 20% | BZ | G |
| M49467R05123K | 0.012 μF | 10% | BR | J |
| M49467R05123M | 0.012 μF | 20% | BR | J |
| M49467Z05123K | 0.012 μF | 10% | BZ | G |
| M49467Z05123M | 0.012 μF | 20% | BZ | G |
| M49467R05153K | 0.015 μF | 10% | BR | J |
| M49467R05153M | 0.015 μF | 20% | BR | J |
| M49467Z05153K | 0.015 μF | 10% | BZ | J |
| M49467Z05153M | 0.015 μF | 20% | BZ | J |
| M49467R05183K | 0.018 μF | 10% | BR | K |
| M49467R05183M | 0.018 μF | 20% | BR | K |
| M49467Z05183K | 0.018 μF | 10% | BZ | J |
| M49467Z05183M | 0.018 μF | 20% | BZ | J |
| M49467R05223K | 0.022 μF | 10% | BR | K |
| M49467R05223M | 0.022 μF | 20% | BR | K |
| M49467Z05223K | 0.022 μF | 10% | BZ | K |
| M49467Z05223M | 0.022 μF | 20% | BZ | K |
| M49467Z05273K | 0.027 μF | 10% | BZ | K |
| M49467Z05273M | 0.027 μF | 20% | BZ | K |
| M49467Z05333K | 0.033 μF | 10% | BZ | K |
| M49467Z05333M | 0.033 μF | 20% | BZ | K |

**CALL PRESIDIO FOR  
CROSS REFERENCE P/N'S**

### MIL-PRF-49467 PART NUMBER REFERENCE

**M49467**  
Performance Specification  
Indicating MIL-PRF-49467

**R**  
Characteristic  
(1.2.1.1)

**01**  
Performance Specification  
Sheet Number Indicating  
MIL-PRF-49467/1

**101**  
Capacitance Value  
(1.2.1.2)

**K**  
Capacitance  
Tolerance  
(1.2.1.3)



**PRESIDIO COMPONENTS, INC.**

7169 Construction Court, San Diego, CA 92121 • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225

www.presidiocomponents.com • info@presidiocomponents.com